

Differential Sub Ported DYNAWELL



Technical Information

SPECIFICATIONS:

PRESSURE RATING
68.9 MPa 10,000 psi

TEMPERATURE RATING 204 °C / 399.2 °F
DEPENDING ON O-RING TYPE, SPECIFY
WELL TEMPERATURE ANTICIPATED WHEN
ORDERING

DESIGNED TO MAINTAIN A HIGH
DIFFERENTIAL PRESSURE IN FAVOUR OF
THE ANNULUS (UNDERBALANCE), WHILE
KEEPING FLUID FROM ENTERING THE
TUBING PRIOR TO GUN INITIATION.

RECOMMENDATIONS:

IN ORDER TO ENSURE THE PROPER
OPERATION IT IS RECOMMENDED TO USE
THE APPROPRIATE REDRESS KITS FOR
EACH RUN

AVAILABLE SIZES:

OTHER SIZES AVAILABLE ON REQUEST

Manufactured by LRI

Size	60mm / 2.375"	73mm / 2.875"
Maximum O.D.	78mm / 3.062"	93mm / 3.668"
Connection	2 3/8" EU PIN	2 7/8" EU PIN
Minimum I.D.	50.7mm / 1.995"	62mm / 2.441"

Revision: RP04010AA

Selection Chart

Part No.	Size (mm / in)	Max. O.D. (mm / in)	Weight (kg)	Dimensions (mm)	Part No. Redress Kit
2316776	60mm / 2.375"	78mm / 3.062"	4.6	307.0 x 78.0	2316777
2316799	73mm / 2.875"	93mm / 3.668"	7.0	318.0 x 93.0	2316800