

## Differential Sub Non Ported DYNAWELL



### Technical Information

**SPECIFICATIONS:**

PRESSURE RATING  
68.9 MPa 10,000 psi

TEMPERATURE RATING 204 °C / 399.2 °F  
DEPENDING ON O-RING TYPE, SPECIFY  
WELL TEMPERATURE ANTICIPATED WHEN  
ORDERING

DESIGNED TO MAINTAIN A HIGH  
DIFFERENTIAL PRESSURE IN FAVOUR OF  
THE ANNULUS (UNDERBALANCE), WHILE  
KEEPING FLUID FROM ENTERING THE  
TUBING PRIOR TO GUN INITIATION.

**RECOMMENDATIONS:**

IN ORDER TO ENSURE THE PROPER  
OPERATION IT IS RECOMMENDED TO USE  
THE APPROPRIATE REDRESS KITS FOR  
EACH RUN

**AVAILABLE SIZES:**

OTHER SIZES AVAILABLE ON REQUEST

Manufactured by LRI

<b>Size</b>	<b>60mm / 2.375"</b>	<b>73mm / 2.875"</b>
<b>Maximum O.D.</b>	78mm / 3.062"	93mm / 3.668"
<b>Connection</b>	2 3/8" EU PIN	2 7/8" EU PIN
<b>Minimum I.D.</b>	50.7mm / 1.995"	62mm / 2.441"

Revision: RP04010AA

### Selection Chart

Part No.	Size (mm / in)	Max. O.D. (mm / in)	Weight (kg)	Dimensions (mm)	Part No. Redress Kit
2316770	60mm / 2.375"	78mm / 3.062"	4.7	307.0 x 78.0	2316777
2316801	73mm / 2.875"	93mm / 3.668"	7.1	318.0 x 93.0	2316800