

Wellhead Potential Monitor DYNAWELL

Item	Part No.	Weight	Dimensions
Wellhead Potential Monitor	2315907	2.400 g	48.0 x 9.0 x 25.0 cm



Technical Information

SPECIFICATIONS:

DESIGNED TO CONTINUOUSLY MEASURE THE POTENTIAL DIFFERENCE BETWEEN WELLHEAD AND UNIT / TRUCK CHASSIS

CONTINUOUS L.E.D. DISPLAY OF POTENTIAL

AUDIBLE ALARM PRE-SET AT 0.5 VOLT RMS

INCLUDES REMOVABLE SAFETY KEY WITH "PERF-SAFE-LOG" POSITION

PANEL CAN BE POWERED BY TRUCK BATTERY OR 100 TO 250 VAC MAIN SUPPLY

PANEL CIRCUITS CONFORM TO API RP57 RECOMMENDED PERFORATING PRACTISES

DESIGNED FOR 19" RACK MOUNT

MIN TEMPERATURE	5	°C
MAX TEMPERATURE	50	°C

AVAILABLE SIZES:

ONE SIZE AVAILABLE FOR ALL SYSTEMS

RECOMMENDATIONS:

ASSURE GOOD GROUNDING

CHECK FUNCTION BEFORE EACH USE

Revision: FP06007AA