


TCP Safety Impact Sub DYNAWELL



Technical Information

SPECIFICATIONS:

DESIGNED TO REDUCE AXIAL SHOCK WAVES INITIATED BY THE PERFORATING IMPACT

AVAILABLE SIZES:

SEE SELECTION CHART BELOW

RECOMMENDATIONS:

ALWAYS CHECK ID AND OD BEFORE USE
CHECK IF THREADS ARE MADE UP TO CORRECT MAKE UP TORQUE

ITEM No. (Quantität)	ITEM NAME (Zusatzname)	DESCRIPTION	ITEM No. (Quantität)	ITEM NAME (Zusatzname)	DESCRIPTION
1	CONNECTION	HEAD END - 1/2" EUE - 1/2" EUE - 1/2" EUE	1	CONNECTION	HEAD END - 1/2" EUE - 1/2" EUE - 1/2" EUE
2	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE	2	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE
3	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE	3	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE
4	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE	4	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE
5	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE	5	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE
6	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE	6	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE
7	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE	7	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE
8	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE	8	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE
9	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE	9	CONNECTION	CONNECTION - 1/2" EUE - 1/2" EUE - 1/2" EUE
10	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE	10	WELDED	WELDED - 1/2" EUE - 1/2" EUE - 1/2" EUE

Revision: FP04022AA

Selection Chart

Part No.	Size (mm / ")	Maximum (mm / ")	Minimum ID (mm / ")	Thread type	Length (mm / ")	Weight (kg)	Dimensions (cm)
2635687	60,3 / 2 3/8	88.9 / 3.50	50.7 / 2.0	EUE	/	/	/
2315372	73 / 2 7/8	106.7 / 4.2	62.0 / 2.44	EUE	/	/	/