


TCP Safety Impact Sub DYNWELL



Technical Information

SPECIFICATIONS:

DESIGNED TO REDUCE AXIAL SHOCK WAVES INITIATED BY THE PERFORATING IMPACT

AVAILABLE SIZES:

SEE SELECTION CHART BELOW

RECOMMENDATIONS:

ALWAYS CHECK ID AND OD BEFORE USE
CHECK IF THREADS ARE MADE UP TO CORRECT MAKE UP TORQUE

D-5/8 EUE - 5/8" VERTICAL SAFETY ASSEMBLED SUB (PART 2317667)		D-5/8 EUE - 5/8" VERTICAL SAFETY ASSEMBLED SUB (PART 2317668)	
ITEM NO.	DESCRIPTION	ITEM NO.	DESCRIPTION
1	CONNECTOR	1	CONNECTOR
2	WASHER	2	WASHER
3	WASHER	3	WASHER
4	WASHER	4	WASHER
5	WASHER	5	WASHER
6	WASHER	6	WASHER
7	WASHER	7	WASHER
8	WASHER	8	WASHER
9	WASHER	9	WASHER
10	WASHER	10	WASHER

Revision: ET04022AB

Selection Chart

Part No.	Size (mm / ")	Maximum (mm / ")	Minimum ID (mm / ")	Thread type	Length (mm / ")	Weight (kg)	Dimensions (cm)
2317667	60,3 / 2 3/8	88.9 / 3.50	50.7 / 2.0	EUE	/	/	/
2317668	73 / 2 7/8	106.7 / 4.2	62.0 / 2.44	EUE	/	/	/